# High Performance, **Easy Assembly**

Sani-Matic Basket Strainers are specially constructed to strain particulates out of a high volume process stream.

The innovative, durable design includes a side-inlet, which

allows you to easily remove the basket for cleaning without disconnecting the line.

Our Basket Strainers can be equipped with either a wedgewire or perforated basket with a woven cloth insert bag for finer straining applications. Filter bags are available in a wide variety



Sani-Matic's standard Basket Strainers are 3-A approved when using the perforated insert. If a 3-A approval is required, your sales representative

should be consulted to ensure the configuration meets 3<sup>1</sup>A standards.

#### **Standard Features**

- Cast and heavy gauge T316L stainless steel construction
- The lid and hand knob closure are rated for higher pressures than clamp-style covers for improved worker safety
- Quick release hand knobs and hinged lid remain attached for convenient operation
- Machined o-ring seat prevents any fluid bypass and improves reliability
- Air relief vent valve included with complete assembly
- Rated to 100 psi maximum @ 200° F
- Available in five fitting sizes
- Choose wedgewire or perforated strainer elements

#### **Options**

- Disposable filter bags in various media types and sizes for perforated and wedgewire models with media clamp and ring
- Long and short strainer stands available

#### Complete **Assembly** with Perforated Strainer **Element**

(specify hole size when ordering: 1/8", 3/16" or 1/4")

Fitting Size "'Uj qtv'Part # ""- "'Nqpi 'Part #

2.0""" 2.5" "" 3.0" ""

4.0" '"""\$10520'"""" \$10509

# Complete Assembly with Wedgewire Strainer Element (specify hole size when ordering: 0.005", 0.015" or 0.030")

Fitting Size Uj qtv'Part # - Nqpi 'Part #

1.5	" """S1	0510'"""	""""S10515
			"""10516
****	**********		""'S10517
""""""3.0	" '"""S10	0513 '"""	"""S10518
"""""4.0	" '"""S10	0514 '"""	"""S10519

### Basket

## Strainer

attachment point.

# """"""""""""""""Air Relief Vent Valve

¦¦F gu	et kr vkqp'''	''Rctv'%''''''	"Part #
"Nqpi	'"O qf gn'""'	"963287'""""""""""""""""""""""""""""""""""""	"021881
 ""Long ""Short	Model Model	741065 101998	Standard on all complete assembly units. Air relief vent valve



Side View



Top View



# **Basket Strainer Replacement Parts**

# **Strainer Elements Media Clamp Parts**

#### Description Short Model Long Model Perforated Part # Price Part # Price

1/8" Holes 741039 \$950 741052 \$1,100 3/16" Holes 741040 \$950 741053 \$1,100 1/4" Holes 741051 \$950 741054 \$1,100

#### Wedgewire\* Part # Price Part # Price

0.005" 741022 \$2,100 741047 \$2,300 0.015" 741030 \$2,100 741048 \$2,300 0.030" 741046 \$2,100 741049 \$2,300

\* Other sizes available - please call for quote

### **Elastomers**

#### **Cover O-Ring Part # Price**

EPDM (standard) 021378 \$35

Viton 021144 \$70

#### Element O-Ring Part # Price

EPDM (standard) 021356 \$40

Viton 021143 \$75

#### **Vent Valve Gasket Part # Price**

EPDM (standard) 021037 \$1 Viton 021880 \$3

Cover O-ring and Vent Valve Gasket not pictured

### Disposable Filter Media

50 per Box

			r
-		Old	
Micron	Material		# Part #
Model <sub>l Po</sub>	olypropylene Short S1	10550 029244	
	olypropylene Short S1		
10 Po	lypropylene Short S1	0554 029246	
25 Po	lypropylene Short S1	0556 029247	
50 Po	lypropylene Short S1	0558 029237	
100 Po	lypropylene Short S1	0560 029248	
150 Ny	lon Short S10562 029	9249	
800 Ny	lon Short S10564 029	9250	
1500 Pol	yester Short S10566	029251	
1 Pc	olypropylene Long S1	0551 029252	
5 Pc	olypropylene Long S1	0553 029253	
10 Po	lypropylene Long S1	0555 029254	
25 Po	lypropylene Long S1	0557 029255	
50 Po	lypropylene Long S1	0559 029256	
100 Po	lypropylene Long S10	0561 029257	
150 Ny	lon Long S10563 029	9259	
250 Ny	rlon Long N/A 02626	52 Call	
300 Ny	on Long N/A 02409	98 Call	
800 Ny	don Long S10565 029	9261	

\* All media types rated for 200° F

1500 Polyester Long S10567 029262

\* Please note: Nylon has poor compatibility with some acids and chlorine

### **Description Part # Price** Clamp Ring 641110 \$240 Locking Latch 621766 \$25



Pressure Drop for Basket Strainer

Strainer Size 4"x 22"

6

#### Flow Rate (GPM)

Performance based on testing using 70° F water and 4"x22" housing with 0.005" wedgewire element